

REMARKS

The specification of the subject U.S. patent application, as filed, as constituted by the verified translation of PCT/DE2003/001845, has been cancelled in favor of the concurrently filed substitute specification. A suitable Abstract of the Disclosure has been added. These changes and additions do not constitute any new matter.


Original claims 1-33; claims 1-40 as set forth in the PCT application, as filed; claims 1-33 and claims 1-40 both as set forth in letters from KBA to the European Patent Office, have been cancelled. New claims 41-80 have been added. New claims 41-80 are essentially the same, in scope, as the claims now pending in the PCT application. They have been rewritten more in a form in accordance with U.S. practice and eliminating multiple dependencies.

Entry of this Preliminary Amendment into the file of the subject U.S. patent application, prior to the calculation of the filing fee and prior to an examination of the application on the merits, is respectfully requested.

Respectfully submitted,

Karl Robert SCHÄFER
Kurt Johannes WESCHENFELDER
Applicant

JONES, TULLAR & COOPER, P.C.
Attorneys for Applicant



Douglas R. Hanscom
Reg. No. 26, 600

December 27, 2004
JONES, TULLAR & COOPER, P.C.
P.O. Box 2266 Eads Station
Arlington, Virginia 22202
(703) 415-1500
Attorney Docket: W1.1928 PCT-US

IN THE SPECIFICATION

Please cancel the entire specification of the subject U.S. patent application, as filed, as constituted by the verified translation of PCT/DE2003/001845, including the List of Reference Symbols, in favor of the concurrently filed Substitute Specification. That substitute specification is the result of the entry into the verified translation of a cross-reference to related applications, and of suitable section headings; the deletion of the List of Reference Symbols and of references to the claims, the correction of minor errors in phrasing, grammar and punctuation, and a general revision of the verified translation to place the substitute specification more in a form in accordance with U.S. practice. These various changes and additions do not constitute any new matter. A marked-up copy of the verified translation, which shows the changes made thereto, to arrive at the substitute specification, is submitted for the Examiner's review.

IN THE ABSTRACT

Please add the Abstract of the Disclosure, as set forth on the separate accompanying sheet. That Abstract of the Disclosure is essentially the same, in content, as the Abstract which is a part of the published PCT application WO 2004/002739 A1. No new matter is being presented by the addition of this Abstract of the Disclosure.

[WO 2004/002739]

[PCT/D20E03/001845]

10/517770
DT01 Rec'd PCT/PTC 27 DEC 2004

[SPECIFICATION]

MARKED UP COPY OF SPECIFICATION

SCHÄFER, WESCHENFELDER: W1.1928 PCT-US

**CYLINDER PAIR AND CYLINDER OF A PRINTING UNIT OF A ROTARY
OFFSET PRINTING MACHINE**

CROSS-REFERENCE TO RELATED APPLICATIONS

[001] This U.S. patent application is the U.S. National Phase, under 35
USC 371, of PCT/DE2003/01845, filed June 5, 2003; published as WO
2004/002739 A1 on January 8, 2004, and claiming priority to DE 102 28 968.9,
filed June 26, 2002, the disclosures of which are expressly incorporated herein by
reference.

FIELD OF THE INVENTION

[002] The present invention is directed[relates] to a cylinder pair and to a
cylinder of a printing group of a rotary offset printing press [in accordance with the
preambles of claims 1, 4, 16 or 21]. The cylinder pair consists of a forme cylinder
and a transfer cylinder.

BACKGROUND OF THE INVENTION

[003] A printing group of a rotary printing press having at least one transfer cylinder and at least one forme cylinder is known from WO 01/39977 A1. The[, wherein the] transfer cylinder has a groove for receiving either one or several printing blankets, and the forme cylinder has at least two grooves, which are arranged one behind the other in the circumferential direction, for receiving one or several printing formes. At[, wherein at] least one of the grooves of the forme cylinder is at least partially covered by a printing forme. That[, and wherein the] at least partially covered groove of the forme cylinder rolls off on the area of the groove of the cooperating transfer cylinder intended for receiving one or several printing blankets. The ends of the printing formes can be arranged, offset with[in] respect to each other, in different grooves, or the forme cylinder can have at least two printing formes arranged side-by-side in the axial direction, or can have several printing formes arranged one behind the other in the circumferential direction. In[, wherein in] the case of several printing formes arranged over the

entire circumference, these can also be arranged with their ends alternately arranged offset with[in] respect to each other.

[004] DE 22 20 652 A1 describes a device for fastening flexible printing plates on the plate cylinder of a rotary printing press. The[, wherein the] device has a pair of bracing- clamping cheeks, which are arranged on the same shaft and which are arranged in a cylinder groove in the cylinder body, and are pivotable around a shaft that is extending parallel with the cylinder axis over the entire length of the cylinder. A bracing-clamping cheek pair consists of a bracing cheek and a clamping cheek, wherein the bracing cheek, as well as the clamping cheek working together with it, are seated, pivotable around a shaft which is parallel with the axis and which can be actuated from the front end of the cylinder. In the preferred[exemplary] embodiment described, four bracing-clamping cheek pairs are alternately arranged, once on one half of the cylinder length and again on the other half of the cylinder length. To adapt this prior[the] device to printing plates of different format widths, [it is provided to arrange] a short bracing-clamping cheek pair is arranged as an extension element between two adjoining bracing-clamping

cheek pairs in such a way that it can be connected in the cylinder body with the adjacent bracing- clamping cheek pairs and thus can be pivoted in the same way as the bracing-clamping cheek pairs. Two coaxially arranged connecting shafts are provided in each cylinder groove, which shafts can be rigidly connected with a bracing-clamping cheek pair, that is arranged in one half of the cylinder length, and which shafts permit a torque to be transmitted from the front end, which is a part of the other half of the cylinder, to the bracing-clamping cheek pair which is connected with the connecting shafts. Accordingly, the connecting shafts are pivotably seated in the cylinder groove in the same way as are the bracing-clamping cheek pair connected with them.

[005] A cylinder pair of a rotary printing press, with a 6/2 plate cylinder and with a printing blanket cylinder, is known from DE 25 28 008 A1, A[, wherein the] center set of printing plates is arranged on the plate cylinder and is deliberately offset, at an angle other than 90°, from the two outer sets of printing plates positioned at the ends of the plate cylinder. The[, and the] center printing blanket on the printing blanket cylinder is arranged deliberately offset at an angle other

than 90° from the outer sets of printing blankets at the ends of the blanket cylinder.

The ends of the dressings which are not angled off and which rest on the respective[ly] cylinder, are held by holding devices[means] which are movable in wide cylinder grooves. Ends of dressings, which ends face each other, form a gap between themselves, which gap extends over the width of these dressings.

[006] A device for bracing and/or for clamping flexible plates with angled-off suspension legs, which legs project into a fastening slit of a cylinder used for supporting the plates, is known from DE 199 24 786 A1. The[, wherein the] fastening slit is connected with an axis-parallel cylinder groove in the cylinder radial direction. A[, wherein a] base body, which is open in the direction toward the fastening slit, is arranged in the cylinder groove. Movable[, wherein movable] bracing and/or clamping elements are provided in the interior of the base body. The[, wherein the] base body can consist of several shorter base bodies, which can be coupled together. The base body or bodies, [(ies)] arranged in a row in the cylinder groove, are connected with each other, fixed against relative rotation, [for example] by, for example, [means of] a tooth arrangement. A[, wherein a] first and

a last base body are each[is] connected, fixed against relative rotation, with an end coupling element, whose parts which cover the cylinder groove are fastened on the flanks of the cylinder, for example by the use of screws[screwing].

[007] A cylinder of a web-fed rotary printing press is known from DE 199 01 574 A1. A[, wherein the] shell of the cylinder is divided₁ over its length₁ into adjoining sections, and an opening is provided in each section. This type of construction of a cylinder is not suitable for use in arranging several dressings on the shell of the cylinder along its circumference.

[008] Such a cylinder of single circumference is also known from JP 10-071 694 A. The[, wherein the] forme cylinder and the transfer cylinder are arranged in the printing group in such a way that an opened section of the forme cylinder rolls off on a closed section of the transfer cylinder, and vice versa.

[009] A printing group cylinder₁ with a groove with alternately opened and closed areas arranged on the shell₁ is known from DE 198 54 495 A1. Tongues[, wherein tongues] of a printing forme to be mounted on the printing group cylinder extend into the opened areas.

[010] A cylinder for printing presses is known from DE 696 04 065 T2. A, wherein a] groove, which is open toward the shell, is closed by [means of] an insertion piece, which terminates flush with the shell.

[011] A cylinder of single circumference for printing presses is known from CH 345 906 A. Four[, wherein four] dressings are arranged, side-by-side, on the cylinder in its axial direction. Each[, wherein each] of the dressings is fastened in a bracing groove which is open toward the shell of the cylinder. The[, wherein the] bracing grooves of adjacent dressings are arranged offset in respect to each other along the circumference of the cylinder.

SUMMARY OF THE INVENTION

[012] The object of the present invention is directed to providing[based on creating] a cylinder pair, or to providing a cylinder of a printing group of a rotary offset printing press.

[013] The object is attained in accordance with the invention by the provision of a cylinder pair of a printing group of a rotary offset printing press including a forme cylinder and a transfer cylinder. Both of these cylinders are

divided, in their axial length, into sections and both cylinders are provided with axially extending, dressing end receiving grooves[means of the characteristics of claims 1, 4, 16 or 21].

[014] The advantages which are attainable in accordance with the present invention consist₁ in particular₁ in that openings in the shell of the cylinder are provided only where they are required for holding the dressings. This reduces the danger of a break of one of the dressings₁ in the course of these dressings rolling off against a cylinder against which they are placed. At the same time₁ the effects of the groove beat₁ generated by the cylinder grooves₁ are reduced by the offset arrangement of the grooves. These steps contribute to the provision of quiet running and of reduced vibrations, in particular in connection with cylinders of great length. These steps[, and] therefore also result in an improvement to the print quality. In sections of the grooves₁ which sections are closed against the shell of the cylinders, it is possible to arrange low-cost filler elements₁ without holding assemblies[means] for the dressings₁ in a mounting-friendly manner. In this case₁ the filler elements can be produced in almost every desired length. Since through-

bores, with the required accuracy, can be provided in cylinders of great length
[can] only [be provided with the required accuracy] at great expense, in one
preferred embodiment variation of the present invention, the cylinders have at least
one blind bore extending underneath an outer closed section in the axial direction
of the cylinder.

BRIEF DESCRIPTION OF THE DRAWINGS

[015] Preferred [Exemplary] embodiments of the present invention are
represented in the drawings and will be described in greater detail in what follows.

[016] Shown are in:

Fig. 1, a perspective plan view of a cylinder with two grooves and with four,
side-by-side arranged, dressings in accordance with the present invention, in

Fig. 2, a simplified schematic representation of a printing group with a 6/2
forme cylinder and a transfer cylinder, both of [()single circumference()], in

Fig. 3, a perspective plan view of a dressing, in

Fig. 4, a partial sectional representation of a cylinder with a groove and with

a device for fastening a dressing on a cylinder arranged in the groove[therein], in

Fig. 5, a planar projection[flat development] of four dressings arranged side-by-side offset from each other on a cylinder, and in

Fig. 6, a simplified perspective plan view of a base body or a filler element in accordance with the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[017] A cylinder 01 of a rotary printing press, and in particular a cylinder 01 of a rotary offset printing press, is represented by way of example in Fig. 1. This cylinder 01 can be configured and used[designed] as a forme cylinder 01a or as a transfer cylinder 01b, as seen in Fig. 2, and can be covered, in a[the] circumferential direction of the cylinder 01, with one dressing, for example, and axially, i.e. with[in] respect to a cylinder[its] length L, with four dressings 02a, 02b, 02c, 02d, for example, so that four upright or horizontal dressings are located on the cylinder 01, as is seen in [(]Fig. 5[)].

[018] In connection with the use of cylinder 01 as a forme cylinder, the dressings are preferably configured[designed] as plate-shaped printing formes. In

connection with the use of cylinder 01 as a transfer cylinder, the dressings are preferably configured as rubber printing blankets that are each applied to a support plate, i.e. the dressings for the transfer cylinder are preferably embodied as a metal backed, rubber surfaced printing blanket.

[019] The printing group depicted in Fig. 2 can be configured[designed], for example, as part of a six-cylinder satellite printing group, wherein four cylinder pairs, each cylinder pair consisting of a forme cylinder 01a and of a transfer cylinder 01b, are arranged in a frame, preferably in separate cylinder pairs, and positioned diametrically around a common counter-pressure cylinder in a preferably identical distribution, so that forces acting when the cylinder pairs are placed against the counter-pressure cylinder are mutually supported. The[, wherein the] forme cylinders 01a and the transfer cylinders 01b each have the characteristics directed to[of] the attainment of the object proposed for the present invention[here]. The counter-pressure cylinder, which is not specifically depicted, preferably has a smooth, i.e. closed, outer shell without openings.

[020] Arrangements of cylinder pairs[(Fig. 2)] are advantageous, particular

for newspaper printing, as shown in Fig. 2, wherein a forme cylinder 01a is covered, in its axial direction, in a first semi-circumferential row with, for example, six plate-shaped printing formes 02a, 02b, 02c, 02d, 02e, 02f and, as [-] only schematically depicted[sketched] in [in] Fig. 2, [-] with a second semi-circumferential row, on the side of the forme cylinder 01a which cannot be seen in the representation of Fig. 2, with a further six plate-shaped printing forms 02g, 02h, 02i, 02j, 02k, 02l, so that the forme cylinder 02a has along its length groups off[respectively] two plate-shaped printing formes one behind the other around[along] its circumference. Six such groups or pairs are shown in Fig. 2.

Such a forme cylinder 02a rolls off on or against a transfer cylinder 01b which, for example, is covered axially with three side-by-side arranged rubber printing blankets 02m, 02n, 02o. Each one of these[, wherein each] rubber printing blanket 02m, 02n, 02o essentially extends around[practically covers] the entire circumference of the transfer cylinder 01b. In this example depicted in Fig. 2, the rubber printing blankets 02m, 02n, 02o each have twice the width and twice the length of the respective ones of the plate-shaped printing formes 02a to 02i. The

forme cylinder 01a, which is, for example, covered with a total of twelve plate-shaped printing formes 02a to 02i, and the transfer cylinder 01b which is[covered], for example, covered by a total of three rubber printing blankets 02m, 02n, 02o, here preferably both have the same geometric dimensions with respect to[regarding] the lengths L of their barrels and [of] their circumferences. The[With their respective ends 03, 04, the] plate-shaped printing formes 02a to 02i each have leading and trailing ends 03, 04 which ends are fastened on the forme cylinder 01a in two plate end receiving grooves 11, 12, which grooves 11, 12 are offset by 180° about the circumference of cylinder 01a, for example. The[, while the] respective ends 03, 04 of the rubber printing blankets 02m, 02n, 02o are held in at least one groove 11' of the transfer cylinder 01b, as seen in Fig. 2. The forme cylinder 01a and the transfer cylinder 01b are arranged in the printing group in such a way that their respective grooves roll off on each other, as is also shown in Fig. 2. To complete the picture, it should be noted here that the forme cylinder 01a can also be covered with dressings which are configured[designed] as a panorama printing plate, so that each plate-shaped printing forme contains two print image

pages. In this case, the reference symbols 02a to 02i shown in Fig. 2 for the dressings relate to the print image pages, wherein the print image pages 02a, 02b, or 02c, 02d, or 02e, 02f, or 02g, 02h, or 02i, 02j, or 02k, 02l are respectively both arranged on one panorama printing plate. Each print image page can more typically correspond to a single newspaper page, for example. An arrangement of six such newspaper pages, placed side- by-side in the axial direction of the former cylinder 01a, is advantageous.

[021] If now, as will be described subsequently[later], dressings are arranged offset with[in] respect to each other in the circumferential direction of the cylinder, in the case where panorama plates are being employed, this means that not the individual print pages, but the panorama plates to be fastened on a[the] shell or circumferential surface 13 of the cylinder 01a, each such panorama plate consisting of two print pages, are arranged offset with[in] respect to each other. To make possible such an offset arrangement of dressings, in a cylinder that is configured with two axially extending, circumferentially spaced grooves, the individual panoramic dressings must either each extend completely around the

circumference, wherein both ends of the same dressing are fastened in the same groove, and wherein the ends of an adjoining dressing are fastened in the other groove. Alternatively, [or] more than two grooves will be[are] provided in the cylinder, for example four such grooves may be provided and[which] are each arranged offset circumferentially by 90° with respect to each other, so that respectively two dressings can be arranged one behind the other in respect to the cylinder circumference, for example, and wherein the ends of each dressing are fastened in two different grooves, each offset by 180°, and adjoining dressings are fastened in two other[the] grooves which are offset by 90° in respect to the first two grooves[thereto].

[022] The cylinder 01, 01a, 01b has a diameter D1 of₁ for example 160 mm to 340 mm, and preferably of between 280 mm and 300 mm. The axial length L of the barrel of the cylinder 01, 01a, 01b lies in the range of between 1200 mm and 2400 mm, for example, and preferably of between 1900 mm and 2300 mm, as depicted in [(]Fig. 1[)]. A plate-shaped printing forme, or a support plate for a rubber printing blanket, as seen in Fig. 3, as a rule₁ consists of a flexible, but an

otherwise dimensionally stable material, such as, for example, [of] an aluminum alloy, and has two oppositely located ends 03, 04, which are to be fastened in or on the cylinders 01, 01a, 01b. The plate ends 03, 04 have[of] a material thickness M of, for example, between 0.2 mm to 0.4 mm, and preferably of 0.3 mm. To form suitable plate end[, wherein for forming] suspension legs 06, 07, each of these plate ends 03, 04 is angled off about[along] a bending line 08, 09, and with respect[related] to a plane of the extended length l of the dressings 02a to 02o, at an angle α , β of between 40° and 140°, and preferably of 45°, 90° or 135°, as seen in [(Fig. 3)]. If only a single dressing 02m to 02o has been applied, in the circumferential direction of the cylinder 01b, the length l of the dressing 02m to 02o approximately corresponds to the length of the circumference of the cylinder 01b.

[023] In the preferred embodiment of the present invention, which is[example] represented in Fig. 1, and on which the following explanation of the invention [in what follows] is based, without being limited to this embodiment, a first groove 11 and a second groove 12 are provided in the cylinder 01, wherein both grooves 11, 12 extend continuously in the direction of the length L of the cylinder

01. These two grooves 11, 12[and] are arranged offset with[in] respect to each other in the direction of the circumference of the cylinder 01[latter], for example are offset at a distance defined by an arc of a circle extending over 180°. To avoid an error in balance[a balance error] of the cylinder 01, which is rotating in the printing group, it is advantageous to arrange the grooves 11, 12 in an equidistant manner about the cylinder 01, i.e. at identical distances from each other. A variation of the arrangement of the present invention, with continuous grooves as represented in Fig. 1, consists in that at least one of the grooves 11, 12 only extends over a part of the entire length L of the cylinders 01. This[, wherein this] partial section having a partial groove need not necessarily be arranged at the edge of the circumferential shell 13 of the cylinder 01. Instead, it[, but instead] can also be located between the ends of the cylinder 01 along[in] the interior length of the circumferential shell 13 of the cylinder 01. For reasons of manufacturing technology and for practical reasons, however, it is advantageous to connect a partial groove 11, 12 which is extending only over a part of the length L of the cylinder 01, also with an[a front] end face of the cylinder 01, so that the non-

continuous groove 11, 12 extends under a section of the cylinder circumference which is closed toward the circumferential shell of the cylinder. If, in the example of a 6/2 forme cylinder 01a, such as is represented in Fig. 2, the grooves 11, 12 have an opening 14, as seen in Figs. 4 and 5, leading to the grooves 11, 12 in the circumferential shell 13, for example in the interior section B, in which the dressings 02c, 02d, 02i, 02j are fastened, the grooves 11, 12 can pass either through the section A or C to a front end or end face of the forme cylinder 01a. In this case, the grooves 11, 12 are configured[designed] as blind bores, which are open at a front or end face of the cylinder 01a, 01b, and are provided, for example, for mounting a holding device for the dressings, and which extend over one or two adjoining sections A, B, C of the cylinder 01a, 01b. The mentioned sections A, B, C will be discussed in greater detail in what follows. The width of each of the sections A, B, C, extending in the axial direction of the cylinder 01[91]a, 01b is preferably defined by the width of the corresponding one of the dressings 02m, 02n, 02o on the transfer cylinder 01b.

[024] Both grooves 11, 12 are embodied in the interior of the cylinder 01 at

a radial depth[distance] “a” of, for example from 4 mm to 10 mm, and preferably of 6 mm, under the shell 13 of the latter in the form of a preferably circular bore through the cylinder 01, and each groove 11, 12 has a diameter of, for example from 25 mm to 50 mm, and preferably of 30 mm. The ratio of the diameters D1, D2 of the cylinder 01 and of the groove 11, 12 therefor[e] is preferably 10:1. If the cross-sectional shape[surface] of the grooves 11, 12 is not circular, a[the] ratio of the cross-sectional surfaces of the cylinder 01 and of one of the grooves 11, 12 is preferably 100:1, so that the cross-sectional surface of the grooves 11, 12 is comparatively small in respect to that of the cylinder 01.

[025] In the configuration[example] represented in Fig. 1, both grooves 11, 12 have been divided₁ in their longitudinal direction₁ in as many sections A, B, C, D as there are dressings 02a, 02b, 02c, 02d which can be arranged side-by-side on the shell 13 of the cylinder 01. The[, wherein the] division [into sections] of the shell 13 into sections corresponds to that of the grooves 11, 12. In some of their sections A, B, C, D, the grooves 11, 12 each may have a narrow, slit- shaped opening 14 extending to the circumferential shell 13 of the cylinder 01, as shown in

[Fig. 4(5)]. It is advantageous if, with[in] respect to the same section A, B, C, D, a groove 11, that is provided with an opening 14, alternates, in the circumferential direction of the cylinder 01, with a groove 12 which is closed toward the shell 13 of the cylinder 11. In this way, an alternating arrangement of openings 14 in the sections A, B, C, D, in relation to the grooves 11, 12 results in the circumferential direction, as well as in the axial direction[,] of the cylinder 01.

[026] A[The] slit width S of the opening 14 is less than 5 mm and preferably lies within the range of 1 mm to 3 mm, as is also shown in [Fig. 4()].

[027] As can be seen in Fig. 5, in this preferred embodiment of the present invention,[example] the number of the sections A, B, C, D, which are arranged side-by-side in the longitudinal direction in each groove 11, 12 and which are provided with an opening 14, corresponds to one half of the dressings 02a, 02b, 02c, 02d, which are arranged circumferentially offset, in respect to each other, over the length L of the cylinder 01. If the shell 13 of the cylinder 01 is covered with more than one side-by-side dressing in the circumferential direction, more than two grooves or partial areas of grooves, each distanced on a defined arc of a

circle, are provided, and complex cover arrangements result on the shell 13 of the cylinder 01 because of the larger number of dressings.

[028] In this depicted embodiment[example], for the sake of simplicity, the number of the dressings 02a, 02b, 02c, 02d and of the sections A, B, C, D was selected as being four each, and wherein each cylinder section A, B, C, D [here] has $\frac{1}{4}$ the length L of the cylinder 01. As indicated in Fig. 5, in a developed representation of the shell 13 of the cylinder 01, all of the four dressings 02a, 02b, 02c, 02d positioned on the shell 13 of the cylinder 01, are arranged side-by-side in the axial direction, and the two axially spaced dressings 2b and 02d are arranged offset, with[in] respect to the two axially spaced dressings 2a and 2c in such a way that these dressings 02b and 02d cover the sections B and D of the groove 12, while the dressings 2a and 2c cover the sections A and C of the groove 11. The groove 11 has an opening 14 to the circumferential shell 13 of the cylinder 01 only in sections B and D, while the groove 12 has an appropriate openings 14 to the circumferential shell in each of the sections A and C. In this example, the dressings 02a, 02b, 02c, 02d each enclose the entire circumference of the cylinder

01. Therefore both of the ends 03, 04 of the dressings 02a, 02c are fastened in the same groove 12, while both of the ends 03, 04 of the dressings 02b, 02d are fastened in the other groove 11. Thus, each dressing 02a, 02b, 02c, 02d covers one of the two grooves 11, 12 in each section A, B, C, D, while it is fastened with its two ends 03, 04 in the other one of the two[another] grooves 11, 12. In this embodiment[example], each section with an opening 14 adjoins a section that is closed toward the shell 13 of the cylinder 01 with[in] respect to a line that is extending obliquely through all cylinder sections A, B, C, D and on the shell 13 of the cylinder 01, parallel with a groove 11, 12, and whose position is predetermined by the position of a groove 11, 12. The openings 14 cut into the shell 13 of the cylinder 01 are aligned with each other along this line.

[029] The suspension legs 06, 07 formed at the ends 03, 04 of each dressings 02a to 02o are inserted into the respective opening 14. It is advantageous to suspend one suspension leg 06 of each dressings 02a to 02o positively connected with a first wall 17 of the opening 14, as seen in Fig. 5, wherein this first wall 17 extends from an outer or circumferential edge 16 of the

opening 14, and which first wall 17 leads₁ in the production direction P of the cylinder 01, 01a, 01b₁ toward the interior of the groove 11', 11, 12. An[The] angle α formed at an end 03 of the dressings 02a to 02o preferably corresponds to an[the] angle α resulting between this first wall 17 extending toward the interior of the groove 11', 11, 12 and an imagined tangent line T resting on the opening 14₁ again as depicted in Fig. 5. The other suspension leg 07 of each dressing 02a to 02o can also be placed against a second wall 19 of the opening 14. This[, wherein this] second wall 19 extends from an outer or circumferential edge 18 of the opening 14, which trails the edge 16 in the production direction P of the cylinder 01, 01a, 01b toward the interior of the groove 11', 11, 12. Again, an[the] angle β formed on an end 04 of the dressing 02a to 02o advantageously corresponds to an[the] angle β which results between this second wall 19 extending toward the interior of the groove 11', 11, 12 and an imagined tangent line T resting on the opening 14, as depicted in [)]Fig 3. and in Fig. 4[)].

[030] As represented in Fig. 4, a holding device is provided for fastening the dressings 02a to 02o on the circumferential shell 13 of the cylinder 01, 01a,

01b in those sections A, B, C, D of the groove 11', 11, 12, which have an opening 14 toward the circumferential shell 13. The[, wherein the] holding device consists, for example, of at least a holding means 21, in the form of, for example, a clamping element 21 and of a spring element 22. The suspension leg 07, shown in [(Fig. 03)] at the trailing end 04 of the dressings 02a to 02o, and which is suspended in the opening 14, is preferably placed against the second wall 19 of the opening 14 and is pressed against this second wall 19 [it there] by the clamping element 21 with a force F which is exerted by the spring element 22 on the clamping element 21. An actuating device[means] 23 is provided in the groove 11', 11, 12 for use in releasing the clamping element 21 which actuating device 23, when actuated, counteracts the force F exerted by the spring element 22 on the clamping element 21 and pivots the clamping element 21 away from the second wall 19 of the opening 14.

[031] To facilitate[For] easier mounting of the above-described holding device in the groove 11', 11, 12, [it is provided to arrange] the holding device, which preferably consists of a clamping element 21 and a spring element 22, is arranged

in a base body 24. This[, wherein this] base body 24 is preferably [is] embodied substantially in the form of a cylindrical hollow body, whose exterior diameter [D3] is slightly less than a[the] diameter D2 of a groove 11', 11, 12, and which base body 24 is supported in the groove 11'; 11, 12 by [means of] its shape, and wherein the clamping element 21 is pivotably seated in the interior of, or on the bottom 27 of this base body 24. It is advantageous to combine the support of the base body 24 in the groove 11', 11, 12 with a securing device to counteract any [against] torsion of the base body 24. For[in that, for] example, a stop may be[is] formed on the base body 24, which stop is supported, for example, in the groove 11', 11, 12, or against one of the walls 17, 19 extending to the edges 16, 18 of the opening 14. Due to[Because of] the considerable length of the sections A, B, C, D, each of which varies₁ in its size₁ as a function of the length L of the barrel of the respective cylinder 01, 01a, 01b, and to facilitate[For the] easier matching to each position required for them₁ [it has been provided to design] the base body 24 required for each section A, B, C, D is configured not in one piece, but instead [to produce] the base body 24 is produced in the form of a partial element, which is

short in comparison with the lengths of the sections A, B, C, D, of a length l1.

Several[, wherein then several] identical base bodies 24 are then lined up in the groove 11', 11, 12 for the required length of the sections A, B, C, D. Each[For its preferably positive connection, each] base body 24 can be provided, at its front end, with a groove-and-tongue connection 28, 29, or with a plug connection to facilitate positive connection. The length l1 of the base body 24, produced as a partial element, can be between 30 mm and 100 mm, for example, and preferably is 60 mm, as seen in [(Fig. 6)].

[032] In the sections A, B, C, D of the cylinder 01, in which no holding device for fastening a suspension leg 06, 07 of one of the dressings 02a to 02o is needed, typically[i.e. as a rule] in the sections A, B, C, D without an opening 14, the introduction of a base body 24 provided with a holding device into the groove 11', 11, 12 is neither required nor efficient. Filler elements 26, as shown in Fig. 6, are provided for these sections A, B, C, D, and whose outer contours can be similar to the outer contours[those] of the base bodies 24. However[wherein, however], the filler elements 26 do not have a holding device in their interior and

are therefore more cost-effective [(Fig. 6)]. The filler elements 26 are also preferably embodied as comparatively short partial elements, with[in] respect to the length of the sections A, B, C, D, and of a length l2. The[, wherein the] length l2, which is typically the same as a[the] length l1 of the base bodies 24, lies between 30 mm and 100 mm, and can preferably be 60 mm. In this way, groups of approximately five to six base bodies 24 or five to six filler elements 26 are preferably arranged in each section A, B, C, D of a groove 11', 11, 12, and wherein these groups are also [alternatingly] arranged in an alternating manner.

[033] It is advantageous to configure[design] the filler elements 26 in such a way that they can be shortened in a simple processing step, such as, for example, by cutting or sawing, to any desired length. The base bodies[elements] 24, as well as the filler elements 26, are preferably made of a plastic material in the form of an injection-molded element, or of another suitable material, which is easy to work. It is intended to position[arrange] lined-up filler elements 26 in the grooves 11, 12 of all those sections A, B, C, D of cylinder 01 which are closed, i.e. in grooves 11, 12 which have no opening 14 toward the shell 13 of the cylinder 01,

01a, 01b. To accomplish[For connecting] the connection of individual filler elements 26 with each other, or to connect respectively first or last filler elements 26₁ in a row of several filler elements 26₁ with a base body 24 arranged in the same groove 11, 12, the filler elements 26 can have the same groove-and-tongue connection 28, 29, or plug connection, at their [front] end faces 32 as are provided on the base bodies 24. To keep[For keeping] the filler element 26 functional with[in] respect to its connectability with other filler elements 26 or with other base bodies 24₁ following a shortening of its length l2, the groove 28, which is cut into each filler element 26 and[it] of a length l3₁ extends over a large portion of the overall length l2 of the filler element 26. The groove[, wherein the] length l3 can be up to 70% of the overall length l2.

[034] A hose, which can be preferably charged with a pressure medium, such as, for example₁ compressed air, and which can advantageously be placed into the groove 11', 11, 12 continuously from one [front] end face of the cylinder 01, 01a, 01b to the other cylinder end face, is provided as the actuating device[means] 23 for the holding device in the base bodies 24. The hose, which forms[i.e.] the

actuating device[means] 23, is preferably placed in a location where a clamping element 21 must be actuated. Thus, the actuating device[means] 23 for the holding device can preferably be actuated by remote control, in particular pneumatically, so that the holding device changes from a closed operating position, in which it holds at least one end 03, 04 of one of the dressings 02a to 02f, 02g to 02m, 02n, 02o, as shown in Fig. 4 into an open operating position.

[035] It is advantageous to also configure[design] the filler elements 26 as substantially cylindrical hollow bodies. With this configuration[design], the base bodies 24, as well as the filler elements 26, have a through-hole 31, through which the hose 23 can be conducted in [case of] a line-up of the base elements 24 and the filler elements 26 in the same groove 11, 12. If[In particular, if] the through-hole 31 is situated[arranged] off-centered in the base bodies 24 and the filler bodies 26, or is asymmetrically located[designed] in respect to a line S_y extending through their respective centers O, and wherein the center O and the line S_y extending through it are located in the same cross-sectional plane X - X, because of its arrangement or shape, the groove-and-tongue connection 28, 29 or the not

depicted plug connection can be used for aligning the through[trough]-hole 31 of the base bodies 24 as well as of the filler elements 26 flush with each other, as well as with[in] respect to each other. If the base bodies 24 are arranged, each fixed against relative rotation, in the groove 11, 12, a sufficient protection against twisting of the filler elements 26 is also accomplished[achieved] because of the positive connection of all of the base bodies 24 arranged in the same groove 11, 12. If necessary, the same protection against twisting, as is provided on the base bodies 24, can be formed on the filler elements 26 [as on the base elements 24].

An actuating device[means] 23, such as the depicted hose, and arranged continuously extending from the one to the other [front] end of the cylinder 01, 01a, 01b permits the simultaneous and mutual actuation of the holding device in several base bodies 24, which are arranged in the same groove 11', 11, 12. It is advantageous to insure[assure] that at least all of the holding devices, which are arranged in the same section of the plural sections A, B, C, D of a groove 11', 11, 12, can be actuated simultaneously [and] together. This embodiment results in holding devices arranged in different sections A, B, C, D to be actuated section-by-

section. These holding devices in each section[, and they] therefore maintain their own open operating position or their own closed operating position independently of each other. It is thus possible to maintain or to release dressings 02a to 02o in different sections A, B, C, D individually and independently of each other.

[036] In a further preferred[exemplary] embodiment of the present invention, at least the actuating device[means] 23 is configured[are designed] as a spindle, for example as an eccentric spindle, that is arranged in the groove 11', 11, 12. If necessary, a clamping element 21 can be formed directly on the spindle, or can be connected with it. By application[means] of a torque acting on the spindle from the direction of an[a front] end of the cylinder 01a, 01b, one or several of the holding devices can be actuated in the grooves 11', 11, 12. For example, a spindle can extend from an[a front] end face of the cylinder 01a, 01b in the groove 11', 11, 12 through a section A or C, which, as shown in [(Fig. 2)], is arranged at the edge or end of the cylinder 01, 01a, 01b, which does not have an opening 14 extending toward the circumferential shell 13 of the respective cylinder 11', 11, 12 and which has a holding device in the section B which, in the respective groove [in question]

11', 11, 12 has an opening 14 toward the shell 13 of the cylinder 01a, 01b. In, wherein in] this section B, the groove 11', 11, 12, that is configured[designed] as a blind bore, as well as the actuating device[means] 23, or the spindle, terminate in this groove 11', 11, 12. It can also be provided that in the same groove 11', 11, 12, for example in the sections A and C, individual spindles can be[are] inserted, which individual spindles can each be actuated from the [front] end face of the cylinder 01a, 01b. These[, wherein these] sections A, C each have an opening 14 toward the shell 13 of the cylinder 01a, 01b. Neither[, while neither] an opening 14 nor a groove 11', 11, 12, or an actuating device[means] 23, or a spindle, are provided in section B. In case of a cylinder 01, 01a, 01b with more than three sections A, B, C in its axial direction, a groove 11', 11, 12, which is embodied as a blind bore, can also tunnel underneath a section B, C, which does not lie directly at an edge of the cylinder 01, 01a, 01b and which is closed toward the shell 13.

[037] Regardless of how the groove 11', or the grooves 11, 12, in the cylinders 01, 01a, 01b are structured[designed], whether they extend continuously from one to the other [front] end face of the cylinder 01, 01a, 01b, or whether they

are [only] embodied as partial elements in the respective sections A, B, C, D, in accordance with the attainment of the object of the present invention[proposed here], it is sufficient[valid] for a cylinder 01, 01a, 01b₁ having a circumference U, as well as having a length L, and wherein the shell 13 of the cylinder 01, 01a, 01b is divided into at least three adjoining sections A, B, C over the length L, that the shell 13 in each of at least three sections A, B, C has a slit-shaped opening 14 and wherein, in relation to the circumference U of the cylinder 01, 01a, 01b₁ at least two openings [(14)] of a section A, B, C, D, are arranged offset with[in] respect to the openings 14 of another section A, B, C, D. In this case, preferably two openings 14, which are arranged in two different sections A, B, C, D₁ are aligned with each other. Here, every opening 14 opens into at least a partial element of a groove 11', 11, 12 extending underneath the shell 13 of the cylinder 01, 01a, 01b.

[038] A[Using a cylinder 01, 01a, 01b in accordance with the invention, a] printing group of a rotary offset printing press, and using a cylinder 01, 01a, 01b in accordance with the present invention, results, for example, in the printing group having at least one forme cylinder 01a rolling off on a transfer cylinder 01b,

wherein the forme cylinder 01a has at least two dressings 02a to 02l axially, as well as around[along] its circumference U, for example, and the transfer cylinder 1b has at least two dressings 02m to 02o axially, for example, and wherein at least two of the dressings 02a to 02l arranged along its circumference U are arranged offset with[in] respect to each other. In this case₁ the forme cylinder 01a preferably has at least four dressings 02a to 02l arranged side-by-side axially, and wherein the at least four dressings 02a to 02l are arranged offset₁ in pairs₁ in the axial direction of the forme cylinder 01a. The forme cylinder 01a can₁ in particular₁ have six dressings 02a to 02l, which are arranged offset with[in] respect to each other₁ in pairs₁ in the axial direction of the forme cylinder 01a. In a printing group of this type, the dressings 02m to 02o of the transfer cylinder 01b are preferably as long, measured along the transfer cylinder 01b[relating to its] circumference U, as two dressings 02a to 02l of the forme cylinder 01a, measured along that cylinder circumference, so that a forme cylinder 01a of double circumference and a single-circumference transfer cylinder 1b work together with each other and roll off on each other.

[039] As previously described, it is of advantage to configure[design] this printing group as a 9-cylinder satellite printing unit. In[For] a printing group having[with] cylinders of great length, for example of a length of up to 2400 mm, wherein the printing group has a forme cylinder which preferably prints six newspaper pages side-by-side in its axial direction and also has a transfer cylinder of corresponding length working together with the forme cylinder, there is[has] a considerable tendency, in particular at high rotary speeds, toward interfering cylinder bending fluctuations, which negatively affect the print quality and which are even increased by the groove or channel beat between the forme cylinder and the transfer cylinder. It is therefore advantageous to employ such cylinders of great length particularly in [particular in] a 9-cylinder satellite printing unit. Every[, because every] transfer cylinder in such a 9-cylinder satellite printing unit can be supported by a central counter-pressure cylinder. The[, wherein the] counter-pressure cylinder is, in turn, supported by a second transfer cylinder, which is arranged diametrically opposite with[in] respect to the first transfer cylinder. Customarily, the counter-pressure cylinder has a smooth closed shell, which

closed shell completely supports the transfer cylinder [completely] on its surface.

This arrangement, together with the groove beat-reducing offset of the center rubber printing blanket with[in] respect to the two outer rubber printing blankets, assures a high degree of reduced vibrations, of quiet running, and therefore of high print quality. Thus, the advantage to be gained by [means of] the present invention consists, in particular, in that it is possible to configure[design] a vibration-reduced printing group even in connection with cylinders of great length, and in which[wherein] steps taken in connection with the cylinder can be advantageously realized by manufacturing technology.

[040] While preferred embodiments of a cylinder pair and cylinders of a printing unit of a rotary offset printing machine, in accordance with the present invention, have been set forth fully and completely hereinabove, it will be apparent to one of skill in the art that changes in, for example, drives for the cylinders, a source of air under pressure, and the like could be made without departing from the true spirit and scope of the present invention which is accordingly to be limited only by the appended claims.

[WO 2004/002739]

[PCT/D20E03/001845]

WHAT IS CLAIMED IS:

[List of Reference Symbols

01	Cylinder
01a	Forme cylinder
01b	Transfer cylinder
02a to 02l	Dressing, printing forme
02m to 02o	Dressing, printing forme, rubber printing blanket
03, 04	Ends
05	-
06, 07	Suspension legs
08, 09	Bending line
10	-
11', 11, 12	Grooves
13	Shell
14	Opening
15	-
16	Leading edge
17	First wall
18	Trailing edge
19	Second wall
20	-
21	Holding means, clamping element
22	Spring element
23	Actuating means, hose, spindle
24	Base body
25	-
26	Filler element
27	Bottom (24)
28	Groove
29	Tongue
30	-]

[31	Through-hole
32	Front end
A, B, C, D	Sections
D1	Diameter of the cylinder
D2	Diameter of the grooves
D3	Exterior diameter
U	Circumference of the cylinder
M	Thickness of the material
P	Production direction
S	Slit width
F	Force
a	Distance
L	Length
O	Center
Sy	Line
X - X	Cross-sectional plane
l1	Length
l2	Length
L3	Length]